

New for 2017

FLO-MASTER

CENTRAL VACUUM

Performance and Value

Many homes will find Flo-Master the brand of choice. Excellent performance in combination with aggressive pricing makes this model line everything a homeowner desires in a central vacuum.

Engineered to Impress

All Flo-Master models offer quality Ametek motors, quiet operation, a utility valve and a pre-installed air-relief valve to eliminate overheating the thru-flow motor.

Built to Last

Flo-Master is built with 18 and 20 gauge steel, powder-coated inside and out, and features the highest quality electronics. Most Flo-Master units are backed with a 10-year warranty for long term, trouble-free operation. The highly efficient Tru-Seal® Microfiltration keeps the thru-flow motors clean and cool.



Features

- 3 & 10 Year Transferable Warranty Lifetime on Manufacturing
- Capacity of 5 to 8 Gallons
- Filters to .3 Microns 5-Layer Microfiltration
- Ventable Exhaust
- Dual Debris Intake
- Utility Valve Hose Connection
- Two-Stud Brackets Easy to Hang & Remove
- All 18 & 20 Gauge Steel
- Powder Coated

Four Models Available

See Reverse for Details



Designed & Assembled in USA
www.builtinvacuum.com
1-800-525-2055

FLO-MASTER

CENTRAL VACUUM



Flo-Master Models MD Part #	F450t F1153AF	F600t F115EAC	F650t F1156AC	F700t F115DAD
Motor	Single 1-stg. 5.7" thru-flow	Single 2-stg. 5.7" thru-flow	Single 2-stg. 5.7" thru-flow	Single 2-stg. 5.7" thru-flow
Max Air Watts	453	597	650	700
Max Amps	10.2	12.3	15	14.5
Waterlift	108"	128.8"	143.1"	138.1"
CFM @ 2" Opening	119.5	130.6	130.2	137.5
Voltage	120	120	120	120
Height	20"	29"	29"	37"
Weight	15 lbs.	34 lbs.	34 lbs.	38 lbs.
Trash Capacity	5 gal.	8 gal.	8 gal.	8 gal.
Filtration	Closed Bag	Tru-Seal® Microfiltration Closed Bag System		
Suggested Footage	3,000*	6,000*	8,000*	10,000*
Quietness	62dB _A	63dB _A	64dB _A	65dB _A
Warranty	3 year Transferable + Lifetime	10 Year Transferable + Lifetime		
Protection	Resettable Minibreaker			
Construction	18 & 20 Gauge Steel			
Finish	Powder Coat			

Power units also available in 240 volts.

Flo-Master Warranty

M.D. Manufacturing, Inc. warrants its Flo-Master power units against electrical component failure for a period of ten (10) years. This warranty is transferable with the unit and is not solely limited to the original owner. Any parts (excluding filters) required within the first ten years will be furnished free of charge by the Authorized Dealer from whom the power unit was originally purchased. Model F450t is warranted for three (3) years. In addition, all Flo-Master units are guaranteed for life against defects in materials and workmanship.

If an Authorized Dealer is not nearby, M.D. Manufacturing, Inc. will honor and perform required warranty services. The end user must return the unit to the factory freight pre-paid. This warranty does not apply to applications outside of North America, commercial applications, misuse, abuse, acts of God, operating without the filters, or units tampered with by unauthorized personnel.

Exterior Venting

Venting is optional but is required for confined locations.

Air Relief Valve

The air relief valve installed on the side of the unit should be kept clear of objects to let air into the vacuum and must not be removed.

*A central vacuum's square foot coverage should be based on factors including altitude, hours of use, complexity of pipe installation, length of furthest vacuum inlet, noise level desired, type and size of filtration, installation materials, and budget. The square footage recommendation on this page can be higher or lower when taking these factors into consideration.